# July 2025: Top 10 Cited Articles

## International Journal on Soft Computing, Artificial Intelligence and Applications (IJSCAI)

**ISSN : 2319 - 1015 [Online]; 2319 - 4081 [Print]**

**http://airccse.org/journal/ijscai/index.html**



# Big Data Analytics: Challenges And Applications For Text, Audio, Video, And Social Media Data

**Jai Prakash Verma, Smita Agrawal, Bankim Patel and Atul Patel**

**CSE Department, Institute of Technology, Nirma University, Ahmedabad**

## ABSTRACT

All types of machine automated systems are generating large amount of data in different forms like statistical, text, audio, video, sensor, and bio-metric data that emerges the term Big Data. In this paper we are discussing issues, challenges, and application of these types of Big Data with the consideration of big data dimensions. Here we are discussing social media data analytics, content based analytics, text data analytics, audio, and video data analytics their issues and expected application areas. It will motivate researchers to address these issues of storage, management, and retrieval of data known as Big Data. As well as the usages of Big Data analytics in India is also highlighted.

## KEYWORDS

Big Data, Big Data Analytics, Social Media Analytics, Content Based Analytics, Text Analytics, Audio Analytics, Video Analytics.

**Volume URL : https://airccse.org/journal/ijscai/current2016.html**

**Source URL : https://aircconline.com/ijscai/V5N1/5116ijscai05.pdf**

## REFERENCES


[1] Web content available on the link: ―http://www.sas.com/en_us/insights/big-data/what-is-bigdata.html‖ on the dated: 16-08-2015

[2] Web content available on the link: ―http://www-01.ibm.com/software/data/bigdata/what-is-bigdata.html‖ on the dated: 16-08-2015

[3] Web content available on the link: ―http://www.dqindia.com/8-innovative-examples-of-big-datausage-in-india/‖ on the dated: 16-08-2015 International Journal on Soft Computing, Artificial Intelligence and Applications (IJSCAI), Vol.5, No.1, February 2016 50

[4] Web content available on the link: ―http://searchbusinessanalytics.techtarget.com/definition/big-dataanalytics‖ on the dated: 16-08-2015

[5] Web content available on the link: ―https://www.statsoft.com/textbook/text-mining‖ on the dated: 16- 08-2015

[6] Web content available on the link: ―https://www.predictiveanalyticstoday.com/text-analytics‖ on the dated: 16-08-2015

[7] Web content available on the link: ―https://gigaom.com/2014/01/24/why-video-is-the-next-big-thingin-big-data/‖ on the dated: 16-08-2015

[8] Web content available on the link: ―http://searchbusinessanalytics.techtarget.com/definition/socialmedia-analytics‖ on the dated: 16-08-2015

[9] Web content available on the link: ‖http://en.wikipedia.org/wiki/E-commerce_in_India#cite_noteOnline_shopping_touched_new_heights_in_India_in_2012-1‖ on the dated: 16-08-2015.

[10] Amir Gandomi , Murtaza Haider, ―Beyond the hype: Big data concepts, methods, and analytics‖, International Journal of Information Management 35 (2015) 137–144, journal homepage: www.elsevier.com/locate/ijinfomgt

# Bacteria Identification From Microscopic Morphology: A Survey

**Noor Amaleena Mohamad, Noorain Awang Jusoh, Zaw Zaw Htike and Shoon Lei Win**

**Department of Mechatronics Engineering, IIUM, Kuala Lumpur, Malaysia**

## ABSTRACT

Great knowledge and experience on microbiology are required for accurate bacteria identification. Automation of bacteria identification is required because there might be a shortage of skilled microbiologists and clinicians at a time of great need. There have been several attempts to perform automatic background identification. This paper reviews state-of-the-art automatic bacteria identification techniques. This paper also provides discussion on limitations of state- of-the-art automatic bacteria identification systems and recommends future direction of automatic bacteria identification.

## Keywords

Bacteria Identification, Cocci, Bacilli, Vibrio, Naïve Bayes, Machine Learning.

**Volume URL : https://airccse.org/journal/ijscai/current2014.html**

**Source URL : https://airccse.org/journal/ijscai/papers/3214ijscai01.pdf**

## REFERENCES


[1] S.Prabakar, et al., “Development of Image Processing Scheme for Bacterial Classification Based on Optima Discriminant Feature”,Proceedings of the 2010 International Conference of Bioinformatics and Biometrics Engineering, 2010.

[2] L.Frank, “Bacterial Classification, Structure and Function”, 2009, pp.1-2.

[3] Z. Ying, et al., “Bacteria Classification Using Neural Network”, Institute of Biology Gansu Academy of Sciences, 2011.

[4] O.Richard, et al., “Pattern Classification”, 2nd ed., Wiley-Interscience, 2000.

[5] Y. Huiyong, et al., “Research on Insect IdentificationBased on Pattern Recognition Technology”, Taiyuan Extension Station of Application Technology, 2010.

[6] S. Sapna, et al., “Comparative Study of Image Segmentation Techniques and Object Matching Using Segmentation”, Methods and Models in Computer Science, 2009.

[7] T. Wenbing, J.Hai, “Color Image Segmentation Based on Mean Shift and Normalized Cuts”, Man and Cybernetics, 2007.

[8] S.Mohsen, et al., “A Classified and Comparative Study of Edge Detection Algorithms”, Information Technology:Coding and Computing, 2002.

[9] R.Pekka, et al.,“Efficient Automated Method for Image-Based Classification of Microbial Cells”, Department of Chemistry and Bioengineering Tampere University of Technology, 2008.

[10] R.Riries,“Automatic Classification of Tuberculosis Bacteria Using Neural Network”, International Conference on Electrical Engineering and Informatics,2001.

# Deep Learning Sentiment Analysis of Amazon.Com Reviews and Ratings

**Nishit Shrestha and Fatma Nasoz**

**Department of Computer Science, University of Nevada Las Vegas, Las Vegas, Nevada, USA**

## ABSTRACT

Great knowledge and experience on microbiology are required for accurate bacteria identification. Automation of bacteria identification is required because there might be a shortage of skilled microbiologists and clinicians at a time of great need. There have been several attempts to perform automatic background identification. This paper reviews state-of-the-art automatic bacteria identification techniques. This paper also provides discussion on limitations of state- of-the-art automatic bacteria identification systems and recommends future direction of automatic bacteria identification.

## Keywords

Bacteria Identification, Cocci, Bacilli, Vibrio, Naïve Bayes, Machine Learning.

**Volume URL : https://airccse.org/journal/ijscai/current2014.html**

**Source URL : https://airccse.org/journal/ijscai/papers/3214ijscai01.pdf**

# Routing Wireless Sensor Networks Based on Soft Computing Paradigms: Survey

**Marwa Sharawi, Imane Aly Saroit, Hesham El-Mahdy, Eid Emary**

**Faculty of Computer Studies, Arab Open University, Egypt**

## ABSTRACT

Wireless Sensor Networks (WSNs) are defined as dynamic, self-deployed, highly constrained structured network. It`s high computational environment with limited and controlled transmission range, processing, as well as limited energy sources. The sever power constraints strongly affect the existence of active nodes and hence the network lifetime. In order to prolong the network life time we have to overcome the scarcity in energy resources and preserve the processing of the sensor nodes as long as possible. Power management approaches efficiently reduce the sensor nodes energy consumption individually in each sensor node and the adaptive efficient routing technique has greatly appeals a great attention in research. The potential paradigms of soft- computing (SC) highly addressed their adaptability and compatibility to overwhelm the complex challenges in WSNs. This paper is introducing and surveying some of the Soft Computing proposed routing models for WSNs that optimally prolongs its life time.

## KEYWORDS

Wireless Sensor Network, Routing, Soft Computing

**Volume URL : https://airccse.org/journal/ijscai/current2013.html**

**Source URL : https://airccse.org/journal/ijscai/papers/2413ijscai03.pdf**

## REFERENCES


[1] I F Akyildiz, W Su, Y Sankarasubramaniam and E Cayirci (2002) “Wireless sensor networks: a survey”, Computer Networks Vol. 38, No. 4, pp. 393 – 422.

[2] Averkin, A. N., Belenki, A. G., & Zubkov, G. (2007) “Soft Computing in Wireless Sensors Networks”, In Conference of European Society for Fuzzy Logic and Technology (EUSFLAT), No.1, pp. 387-390.

[3] Zheng, J., & Jamalipour, A. (2009)”Wireless sensor networks: a networking perspective”, published by A John & Sons, Inc., Wiley. com

[4] Romer, K., & Mattern, F, (2004)”The design space of wireless sensor networks”, Wireless Communications, IEEE, Vol. 11, No. 6, pp. 54–61.

[5] Yoneki, E., & Bacon, J. (2005)”A survey of Wireless Sensor Network technologies: research trends and middleware’s role”, University of Cambridge TR, 646.

[6] Seah, W. K., Eu, Z. A., & Tan, H. P. (2009)”Wireless sensor networks powered by ambient energy harvesting (WSN-HEAP)-Survey and challenges”, Proceedings of the 1st International Conference on Wireless Communications, Vehicular Technology, Information Theory and Aerospace & Electronic Systems Technology (Wireless VITAE), pp.1-5.

[7] Kulkarni, R. V., Forster, A., & Venayagamoorthy, G. K. (2011)”Computational intelligence in wireless sensor networks: A survey”, Communications Surveys & Tutorials, IEEE, Vol. 13, No. 1, pp. 68 – 96.

[8] A.Alkhatib and G.Baicher, (2012)”An Overview of Wireless Sensor Networks”, 2012 International Conference on Computer Networks and Communication Systems (CNCS 2012) IPCSIT, Vol. 35.

[9] Park, J., & Sahni, S. (2005)”Maximum Lifetime Routing In Wireless Sensor Networks” Computer & Information Science & Engineering, University of Florida.

[10] Datta, N. N., & Gopinath, K. (2006)”A survey of routing algorithms for wireless sensor networks”, Journal of the Indian Institute of Science, Vol. 86, pp. 569-598.

# Fuzzy Logic Based Direct Torque Control of Induction Motor With Space Vector Modulation

**Fatih Korkmaz, İsmail Topaloğlu and Hayati Mamur**

**Department of Electrical and Electronics Engineering Çankırı Karatekin University, 18200, Çankırı, TURKEY**

## ABSTRACT

The induction motors have wide range of applications for due to its well-known advantages like brushless structures, low costs and robust performances. Over the past years, many kind of control methods are proposed for the induction motors and direct torque control has gained huge importance inside of them due to fast dynamic torque responses and simple control structures. However, the direct torque control method has still some handicaps against the other control methods and most of the important of these handicaps is high torque ripple. This paper suggests a new approach, Fuzzy logic based space vector modulation, on the direct torque controlled induction motors and aim of the approach is to overcome high torque ripple disadvantages of conventional direct torque control. In order to test and compare the proposed direct torque control method with conventional direct torque control method simulations, in Matlab/Simulink, have been carried out in different working conditions. The simulation results showed that a significant improvement in the dynamic torque and speed responses when compared to the conventional direct torque control method.

## KEYWORDS

Direct torque control, Fuzzy logic control, Space vector modulation, Induction motor control.

**Volume URL : https://airccse.org/journal/ijscai/current2013.html**

**Source URL : https://airccse.org/journal/ijscai/papers/2613ijscai03.pdf**

## REFERENCES


[1] Cigdem Demir And B'Ulent Yener, "Automated Cancer Diagnosis Based On Histopathological Images: A Systematic Survey", Technical Report, Rensselaer Polytechnic Institute, Department Of Computer Science, Tr-05-09. 1

[2] S. Waheed, R. A. Moffitt, Q. Chaudryl, A. N. Young, and M.D. Wang "Computer Aided Histopathological Classification of Cancer Subtypes", 1-4244-1509-8/07,2007 IEEE.

[3] Olcay Sertel, Umit V. Catalyurek, Hiroyuki Shimada, and Metin N. Gurcan, " Computer-aided Prognosis of Neuroblastoma: Detection of Mitosis and Karyorrhexis Cells in Digitized Histological Images",31st Annual International Conference of the IEEE EMBS Minneapolis, Minnesota, USA, September 2-6, 2009

[4] Ajay Basavanhallya, Elaine Yu, Jun Xu, Shridar Ganesan, Michael Feldman, John Tomaszewski, Anant Madabhushi, "Incorporating Domain Knowledge for Tubule Detection in Breast Histopathology Using O'Callaghan Neighborhoods", Medical Imaging 2011: Computer-Aided Diagnosis, Proc. of SPIE Vol. 7963, 796310, doi: 10.1117/12.878092

[5] Jun Xu, Andrew Janowczyk, Sharat Chandran, Anant Madabhushi, "A Weighted Mean Shift, Normalized Cuts Initialized Color Gradient Based Geodesic Active Contour Model: Applications to Histopathology Image Segmentation", Medical Imaging 2010: Image Processing, Proc. of SPIE Vol. 7623, 76230Y, doi: 10.1117/12.845602

[6] H. Fatakdawala, J. Xu, A. Basavanhally, G. Bhanot, S. Ganesan, M. Feldman, J. E. Tomaszewski, and A. Madabhushi, "Expectation maximization driven geodesic active contour with overlap resolution (emagacor): application to lymphocyte segmentation on breast cancer histopathology," Biomedical Engineering, IEEE Transactions on , In Press. 2009 Ninth IEEE International Conference on Bioinformatics and Bioengineering

[7] Jean-Romain Dalle, Wee Kheng Leow, Daniel Racoceanu, Adina Eunice Tutac, Thomas C. Putti, "Automatic Breast Cancer Grading of Histopathological Images", 30th Annual International IEEE EMBS Conference Vancouver, British Columbia, Canada, August 20-24, 2008

[8] Baochuan Pang, Yi Zhang, Qianqing Chen, Zhifan Gao, Qinmu Peng, Xinge You,"Cell Nucleus Segmentation in Color Histopathological Imagery Using Convolutional Networks", 978-1-4244- 7210-9/10, 2010 IEEE

[9] S. Naik, S. Doyle, S. Agner, A. Madabhushi, M. Feldman, and J. Tomaszewski, "Automated gland and nuclei segmentation for grading of prostate and breast cancer histopathology," in Biomedical Imaging: From Nano to Macro, 2008. ISBI 2008. 5th IEEE International Symposium on, pp. 284– 287, May 2008.

[10] Scott Doyle, Shannon Agner, Anant Madabhushi, Michael Feldman, John Tomaszewski, "Automated Grading Of Breast Cancer Histopathology Using Spectral Clustering with Textural and Architectural Image Features", 978-1-4244-2003-2/08, 2008 IEEE.

# A Study on Graph Storage Database of NOSQL

**Smita Agrawal and Atul Patel**

**1CSE Department, Institute of Technology, Nirma University, Ahmedabad, 2Dean of CMPICA, CHARUSAT University, Changa**

## ABSTRACT

Big Data is used to store huge volume of both structured and unstructured data which is so large and is hard to process using current / traditional database tools and software technologies. The goal of Big Data Storage Management is to ensure a high level of data quality and availability for business intellect and big data analytics applications. Graph database which is not most popular NoSQL database compare to relational database yet but it is a most powerful NoSQL database which can handle large volume of data in very efficient way. It is very difficult to manage large volume of data using traditional technology. Data retrieval time may be more as per database size gets increase. As solution of that NoSQL databases are available. This paper describe what is big data storage management, dimensions of big data, types of data, what is structured and unstructured data, what is NoSQL database, types of NoSQL database, basic structure of graph database, advantages, disadvantages and application area and comparison of various graph database.

## KEYWORDS

Big Data, Graph Database, NoSQL, Neo4j, graph

**Volume URL : https://airccse.org/journal/ijscai/current2016.html**

**Source URL : https://aircconline.com/ijscai/V5N1/5116ijscai04.pdf**

## REFERENCES


[1] Smita Agrawal, Jai Prakash Verma, Brijesh Mahidhariya, Nimesh Patel and Atul Patel , 2015. “Survey On Mongodb: An Open-Source Document Database.International” Journal of Advanced Research in Engineering and Technology (IJARET).Volume:6,Issue:12,Pages:1-11.

[2] Raj, Pethuru, et al. "High-Performance Big-Data Analytics."

[3] Castelltort, Arnaud, and Anne Laurent. "Representing history in graph-oriented nosql databases: A versioning system." Digital Information Management (ICDIM), 2013 Eighth International Conference on. IEEE, 2013.

[4] Bajpayee, Roshni, Sonali Priya Sinha, and Vinod Kumar. "Big Data: A Brief investigation on NoSQL Databases." (2015)

[5] http://neo4j.com/

[6] http://en.wikipedia.org/wiki/Graph_database

[7] E-Book of Graph Database by Ian Robinson, Jim Webber & Emil Eifrem

[8] http://en.wikipedia.org/wiki/NoSQL

[9] http://www.3pillarglobal.com/insights/exploring-the-different-types-of-nosql-databases

[10] http://www.looiconsulting.com/home/enterprise-big-data/

# Pattern Detection with Rare Item-Set Mining

**Mehdi Adda1, Lei Wu2, Sharon White2, Yi Feng 3**

**Computer Science, University of Quebec at Rimouski, Rimouski, Canada**

## ABSTRACT

The discovery of new and interesting patterns in large datasets, known as data mining, draws more and more interest as the quantities of available data are exploding. Data mining techniques may be applied to different domains and fields such as computer science, health sector, insurances, homeland security, banking and finance, etc. In this paper we are interested by the discovery of a specific category of patterns, known as rare and non-present patterns. We present a novel approach towards the discovery of non-present patterns using rare item-set mining.

## KEYWORDS

Data mining, rare patterns, security, intrusion detection, item-set

**Volume URL : https://airccse.org/journal/ijscai/current.html**

**Source URL : https://airccse.org/journal/ijscai/papers/0812ijscai01.pdf**

## REFERENCES


[1] Adda, M., Wu, L., & Feng, Y. (2007). Rare item-set mining. Proceedings of the Sixth International Conference on Machine Learning and Applications (pp. 73–80). Washington, DC, USA: IEEE Computer Society.

[2] Agrawal, R., & Srikant, R. (1994). Fast algorithms for mining association rules in Large Databases. Proceedings of the 20th International Conference on Very Large Data Bases (pp. 487–499). San Francisco, CA, USA: Morgan Kaufmann Publishers Inc.

[3] Agrawal, R., Imieliński, T., & Swami, A. (1993). Mining association rules between sets of items in large databases. Proceedings of the 1993 ACM SIGMOD international conference on Management of data (pp. 207–216). Washington, D.C., United States: ACM.

[4] Amor, N., Benferhat, S., & Elouedi, Z. (2004). Naive Bayes vs decision trees in intrusion detection systems. ACM Symposium on Applied Computing (pp. 420–424). New York: ACM Press.

[5] Barbara, D., Couto, J., Jajodia, S., & Wu, N. (2001). Adam: a testbed for exploring the use of data mining in intrusion detection. Special Section on Data Mining for Intrusion Detection and Threat Analysis , 15–24.

[6] Chan, P., Mahoney, M., & Arshad, M. (2003). A machine learning approach to anomaly detection. Florida Institute of Technology.

[7] Denning, D. (1987). An intrusion-detection model. IEEE Transactions on Software Engineering , 222–232.

[8] DongJun, Z., Guojun, M., & Xindong, W. (2008). An Intrusion Detection Model Based on Mining Data Streams. Proceedings of The 2008 International Conference on Data Mining, DMIN (pp. 398–403). Las Vegas: CSREA Press.

[9] Gou, M., Norihiro, S., & Ryuichi, Y. (2002). A framework for dynamic evidence based medicine using data mining. Proceedings of the 15th IEEE Symposium on Computer-Based Medical Systems (p. 117). Maribor, Slovenia: IEEE.

[10] Haglin, D. J., & Manning, A. M. (2007). On minimal infrequent item-set mining. Proceedings of the 2007 International Conference on Data Mining, DMIN 2007 (pp. 141–147). Las Vegas, Nevada, USA: CSREA Press.

# An SOM-based Automatic Facial Expression Recognition System

**Mu-Chun Su1, Chun-Kai Yang1, Shih-Chieh Lin1,De-Yuan Huang1, Yi-Zeng Hsieh1, andPa-Chun Wang2**

**Department of Computer Science &InformationEngineering,National Central University,Taiwan**

## ABSTRACT

Recently, a number of applications of automatic facial expression recognition systems havesurfaced in many different research fields. The automatic facial expression recognition problem is a very challenging problem because it involves in three sub-problems: 1) face detection, 2) facial expression feature extraction, and 3) expression classification. This paper presents an automatic facial expression recognition system based on self-organizing feature maps, which provides an effective solution to the aforementioned three sub-problems. The performance of the proposed system was computed on twowell-known facial expression databases. The average correct recognition rates were over 90%.

## KEYWORDS

Impulse Noise, Nonlinear filter, Adaptive Filters, Decision Based Filters.

**Volume URL : https://airccse.org/journal/ijscai/current2013.html**

**Source URL : https://airccse.org/journal/ijscai/papers/2413ijscai05.pdf**

## REFERENCES


[1] G. W. Cottrell and J. Metcalfe, "EMPATH: Face, gender, and emotion recognition using holons," Advances in Neural Information Processing Systems, vol. 3, pp. 564-571,1991.

[2] K. Mase, "Recognition of facial expression from optical flow," IEICE Trans., vol. E74, no. 10, pp. 3474-3483,1991.

[3] D. Terzopoulos and K. Waters, "Analysis and synthesis of facial image sequences using physical and anatomical models," IEEE Trans. Pattern Anal. Machine Intell., vol. 15, pp. 569-579,1993.

[4] I. A. Essa and A. Pentland, "A vision system for observing and extracting facial action parameters," in Proc. Computer Vision and Pattern Recognition, pp. 76-83, 1994.

[5] K. Matsuno, C. Lee, and S. Tsuji, "Recognition of human facial expressions without feature extraction," ECCV, pp. 513-520, 1994.

[6] T. Darrel, I. Essa, and A. P. Pentland, "Correlation and interpolation networks for real-time expression analysis/synthesis,"Advancesin Neural Information Processing Systems (NIPS) 7, MIT Press,1995.

[7] Y. Yacoob and L. D. Davis, "Recognizing human facial expressions from long image sequences using optical flow," IEEE Trans.on Pattern Analysis and Machine Intelligence, vol. 18, no. 6, pp. 636-642, 1996.

[8] M.Rosenblum,Y. Yacoob,L.S.Davis, "Human expression recognition from motion using a radial basis function network architecture,"IEEE Trans. on Neural Networks, vol. 7, no. 5, pp. 1121-1138, 1996.

[9] S. Kimura and M. Yachida, "Facial expression recognition and its degree estimation," in Proc. Computer Vision and Pattern Recognition, pp. 295-300, 1997.

[10] C. L. Huang and Y. M. Huang, "Facial expression recognition using model-based feature extraction and action parameters classification," Journal of Visual Communication and Image Representation, vol. 8, no. 3, pp. 278-290, 1997.

# Multi-Population Methods with Adaptive Mutation for Multi-Modal Optimization Problems

**Imtiaz Korejo1, Shengxiang Yang2 (IEEE Member), Kamran Brohi3, Z.U.A.Khuhro4**

**Institute of Mathematics & Computer Science, University of Sindh, Jamshoro,Pakistan**

## ABSTRACT

This paper presents an efficient scheme to locate multiple peaks on multi-modal optimization problems by using genetic algorithms (GAs). The premature convergence problem shows due to the loss of diversity, the multi-population technique can be applied to maintain the diversity in the population and the convergence capacity of GAs. The proposed scheme is the combination of multi-population with adaptive mutation operator, which determines two different mutation probabilities for different sites of the solutions. The probabilities are updated by the fitness and distribution of solutions in the search space during the evolution process. The experimental results demonstrate the performance of the proposed algorithm based on a set of benchmark problems in comparison with relevant algorithms.

## KEYWORDS

Multi-population approaches, adaptive mutation operator, multi-modal function optimization, genetic algorithms

**Volume URL : https://airccse.org/journal/ijscai/current2013.html**

**Source URL : https://airccse.org/journal/ijscai/papers/0413scai01.pdf**

## REFERENCES


[1] P.J. Angeline, (1995) “Adaptive and Self-adaptive evolutionary computations,” In M. Palaniswami and Y. Attikiouzel, editors, Computational Intelligence: A dynamic system perspective, pp. 152- 163. IEEE Press.

[2] T. B¨ack, (1992) “Self-Adaptation in Genetic Algorithms,” In Proc. of the 1st European Conf. on Artificial Life, pp. 263-271.

[3] T. Back and M. Sch¨utz, (1996) “Intelligent mutation rate control in canonical genetic algorithms,” In Foundation of Intellignet Systems, Springer, pp. 158-167.

[4] M. Bessaou, A. Paetrowski, and P. Siarry (2000) “Island model cooperating with speciation for multimodal optimization,” In Proc. of the 6th Int.Conf. on Parallel Problem Solving from Nature, pp. 16-20.

[5] J. Branke, T. Kaubler, C. Schmidt, and H. Schmeck, (2000) “A multi-population approach to dynamic optimization problems,” In Proc. of the 4th Int. Conf. on Adaptive Comput. Des Manuf, pp. 299-308.

[6] L. Davis, (1989) “Adapting operator probabilities in genetic algorithms,” Proc. of the 3rd Int. Conf. on Genetic Algorithms, pp. 61-69.

[7] L. Davis, (1991) “Hankbook of Genetic Algorithms,” Van Nostrand Reinhold.

[8] A.E Eiben, R. Hinterding, and Z. Michalewicz, (1999) “Parameter Control in Evolutionary Algorithms,” IEEE Trans. on Evol. Comput., 3(2): pp. 124- 141.

[9] A.E. Eiben, Z. Michalewicz, M. Schoenauer, and J.E. Smith. (2007) Parameter Control in Evolutionary Algorithms, Parameter setting in Evolutionary Algorithms, Chapter 2, Springer Verlag, pp. 19-46.

[10] T.C. Fogarty, (1989) “Varing the probability of mutation in genetic algorithms,” In Proc. of the 3rd Int. Conf. on Genetic Algorithms, pp. 104-109.

# A Novel Multiplicative Model of Multi Criteria Analysis for Robot Selection

**Bipradas Bairagi1, Balaram Dey2, Bijan Sarkar3 and Subir Sanyal4**

**Department of Production Engineering, Haldia Institute of Technology, Haldia, INDIA**

## ABSTRACT

Selection of an industrial robot for a specific purpose is one of the most challenging problems in modern manufacturing atmosphere. The selection decisions become more multifaceted due to continuous incorporation of advanced features and facilities as the decision makers in the manufacturing environment are to asses a wide varieties of alternatives based on a set of conflicting criteria. To assist the selection procedure various Multiple Criteria Decision Making (MCDM) approaches are available. The present investigation endeavours to mitigate and unravel the robot selection dilemma employing the newly proposed Multiplicative Model of Multiple Criteria Analysis (MMMCA) approach. MMMCA is a novel model in which all performance ratings are converted into numerical values greater than and equal to unity and converting all non-benefit rating into benefit category. Each normalized weight is used as the index of corresponding normalized ratings those are multiplied to obtain the resultant score. The best alternative is associated with the highest resultant score. A real life example is cited in order to demonstrate and validate the applicability, potentiality, suitability, flexibility and validity of the proposed model. At last sensitivity analysis is carried out for making dynamic decision

## KEYWORDS

Multiplicative Model of Multiple Criteria Analysis, Industrial Robot Selection, Sensitivity Analysis

**Volume URL : https://airccse.org/journal/ijscai/current.html**

**Source URL : https://airccse.org/journal/ijscai/papers/1212scai01.pdf**

[1] MacCrimmon, K. R. (1968) “Decision making among Multiple-attribute Alternatives: A Survey and Consolidated Approach”, Memorandum RM-4823-ARPA, Rand Corp., Santa Monica, CA.

[2] Jones, M.S., Malmborg, C.J. & Agee, M.H. (1985) “Decision support system used for robot selection”, Industrial Engineering, Vol. 17, pp.66–73.

[3] Nnaji, B.O. (1988) “Evaluation methodology for performance and system economics for robotic devices”, Computers and Industrial Engineering, Vol.14, pp.27–39.

[4] Agrawal, V.P., Khohl, V. & Gupta, S. (1991) “Computer aided robot selection: the multiple attribute decision making approach”, International Journal of Production Research, Vol. 29, pp.1629–1644.

[5] Chen, S.-H. (1985) “Ranking fuzzy numbers with maximizing set and minimizing set”, Fuzzy Sets and Systems, Vol.17, pp.113–129.

[6] Wang, T.C. & Chang, T.H. (2007) “Application of TOPSIS in evaluating initial training aircraft under a fuzzy environment”, Expert Systems with Applications, Vol.33, pp.870–880.

[7] Kahraman C., Cevik S., Ates N.Y. & Gu¨lbay M. (2007) “Fuzzy multi-criteria evaluation of industrial robotic systems”, Computers & Industrial Engineering, Vol. 52, No.4, pp.414–433.

[8] Narasimhan, R. & Vickery, S.K. (1988) “An experimental evaluation of articulation of preferences in multiple criterion decision-making (MCDM) methods”, Decision Sciences, Vol.19, pp.880–888.

[9] Fisher, E.L. & Maimon, O.Z. (1988) Specification & selection of robots, In A. Kusiak(Ed), Artificial intelligence implications for CIM. Bedboard, UK: IFS Publication.

[10] Boubekri, N., Sahoui, M. & Lakrib, C. (1991) “Development of an expert system for industrial robot selection”, Computers and Industrial Engineering, Vol. 20, pp.119–127.

# Interval Type-2 Fuzzy Logic for Fire Outbreak Detection

**Uduak Umoh1, Udoinyang G. Inyang2, and Emmanuel E. Nyoho3**

**Department of Computer Science, University of Uyo, PMB 1017, Akwa Ibom State,52003, Nigeria**

## ABSTRACT

This paper employed an Interval Type-2 Fuzzy Logic (IT2FL) in the detection of fire outbreak using environmental parameters. Fire outbreak data capturing device (FODCD) is developed and used in capturing environmental parameter values. The FODCD is comprised of DHT11 temperature sensor, MQ-2 smoke sensor, LM393 Flame sensor, and ESP8266 Wi-Fi module connected to Arduino nano v3.0.board. An android application is developed using Android Studio 3.0 to test the functionality of the system. Experimental result indicates that, with the temperature value of 40.657oC, Smoke value of 77.86%, and Flame value of 762.95ppm (part per million), with a threshold T = 0.8, the IT2FL predicted fire outbreak at 0.778 (78%). IT2FL is evaluated using the True Positive Rate (TPR), False Positive Rate (FPR), Accuracy, Error Rate (ER), Precision, and Recall performance metrics. The performance result shows that, the system performs optimally when threshold T is kept between an optimal range of 0.8 and 0.85.

## KEYWORDS

Interval Type-2 Fuzzy Logic, Fire Outbreak Detection, Environmental Parameter, Type Reduction Algorithm

**Volume URL : https://airccse.org/journal/ijscai/current.html**

**Source URL : https://aircconline.com/ijscai/V8N3/8319ijscai03.pdf**

**REFERENCES**

[1] Bezdek, J. (1993). Fuzzy models–what are they, and why? IEEE Trans. on Fuzzy Systems, volume 1, 1-5.

[2] Chu, X. J. (2010). Design of Fire Detection Algorithm Based on Fuzzy Logic and using Wireless Sensors. Canada: Ottawa-Carleton Institute of Electrical and Computer Engineering (OCIECE).

[3] Hagras, H. (2007). Type-2 FLCs: A new generation of fuzzy controllers, IEEE Computational Intelligence Magazine, volume 2, 30-43.

[4] Jantzen, J. (1999). Design Of Fuzzy Controllers. Denmark: Technical University of Denmark, Department of Automation.

[5] Karnik, N. N., Mendel, J. M. (2001). Centroid of a type-2 fuzzy set. Information Sciences, volume 132, 195-220. [6] Khule, V., Jangle, N. N. (2017). Design and implementation of a fire and obstacle detection and control system using fuzzy logic with notification system to avoid automobile accidents. 10th International Conference on Recent Trends in Engineering Science and Management. India: Newton's School of Science and Technology, 307-313.

[7] Liang, Q., Mendel, J. M. (2000). Interval Type-2 Fuzzy Logic Systems: Theory and Design. IEEE Transaction on Fuzzy Systems, volume 8, 535-550.

[8] Mamdani, E. H., Assilian, S. (1975). An experiment in linguistic synthesis with a fuzzy logic controller. International Journal of Man-Machine Studies , 1-13.