

September 2026: Top10 Read Articles in VLSI design & Communication Systems

International journal of VLSI design & Communication Systems (VLSICS)

ISSN : 0976 - 1357 (Online); 0976 - 1527(print)

<https://airccse.org/journal/vlsi/vlsics.html>

[Citations,h-index,i10-index](#)

Citations 3060 h-index 28 i10-index 93

Area, Delay and Power Comparison of Adder Topologies

¹R.UMA, Vidya Vijayan², M. Mohanapriya², Sharon Paul²

¹Research Scholar, Department of Computer Science Pondicherry University,
Pondicherry, India

Department of Electronics and Communication Engineering Rajiv Gandhi College of
Engineering and Technology

ABSTRACT

Adders form an almost obligatory component of every contemporary integrated circuit. The prerequisite of the adder is that it is primarily fast and secondarily efficient in terms of power consumption and chip area. This paper presents the pertinent choice for selecting the adder topology with the tradeoff between delay, power consumption and area. The adder topology used in this work are ripple carry adder, carry look ahead adder, carry skip adder, carry select adder, carry increment adder, carry save adder and carry bypass adder. The module functionality and performance issues like area, power dissipation and propagation delay are analyzed at 0.12 μ m 6metal layer CMOS technology using microwind tool.

KEYWORDS

Ripple Carry Adder, Carry Save Adder, Carry Increment Adder, Carry Select Adder.

For More Details: <https://airconline.com/vlsics/V3N1/3112vlsics13.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol3.html>

REFERENCES

- [1] Animul islam, M.W. Akram, S.D. pable ,Mohd. Hasan, “Design and Analysis of Robust Dual Threshold CMOS Full Adder Circuit in 32 nm Technology”, International Conference on Advances in Recent Technologies in Communication and Computing, 2010.
- [2] Deepa Sinha, Tripti Sharma, k.G.Sharma, Prof.B.P.Singh, “Design and Analysis of low Power 1-bit Full Adder Cell”, IEEE, 2011.
- [3] Nabihah Ahmad, Rezaul Hasan, “A new Design of XOR-XNOR gates for Low Power application”, International Conference on Electronic Devices, Systems and Applications (ICEDSA), 2011.

- [4] R.Uma, "4-Bit Fast Adder Design: Topology and Layout with Self-Resetting Logic for Low Power VLSI Circuits", International Journal of Advanced Engineering Sciences and Technology, Vol No. 7, Issue No. 2, 197 – 205.
- [5] David J. Willingham and izzet Kale, "A Ternary Adiabatic Logic (TAL) Implementation of a FourTrit Full-Adder, IEEE, 2011.
- [6] Padma Devi, Ashima Girdher and Balwinder Singh, "Improved Carry Select Adder with Reduced Area and Low Power Consumption", International Journal of Computer Application, Vol 3.No.4, June 2010 .
- [7] B.Ramkumar, Harish M Kittur, P.Mahesh Kannan, "ASIC Implementation of Modified Faster Carry Save Adder", European Journal of Scientific Research ISSN 1450-216X Vol.42 No.1, pp.53-58,2010.
- [8] Y. Sunil Gavaskar Reddy and V.V.G.S.Rajendra Prasad, "Power Comparison of CMOS and Adiabatic Full Adder Circuits", International Journal of VLSI design & Communication Systems (VLSICS) Vol.2, No.3, September 2011
- [9] Mariano Aguirre-Hernandez and Monico Linares-Aranda, "CMOS Full-Adders for Energy-Efficient Arithmetic Applications", IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol. 19, No. 4, April 2011.
- [10] Ning Zhu, Wang Ling Goh, WeiJa Zhang, Kiat Seng Yeo, and Zhi Hui Kong, "Design of Low-Power High-Speed Truncation-Error-Tolerant Adder and Its Application in Digital Signal Processing", IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol. 18, No. 8, August 2010
- [11] Sreehari Veeramachaneni, M.B. Srinivas, "New Improved 1-Bit Full Adder Cells", IEEE, 2008.
- [12] Tripti Sharma, k.G.Sharma, Prof.B.P.Singh, Neha Arora, "High Speed, Low Power 8T Full Adder Cell with 45% Improvement in Threshold Loss Problem", Recent Advances in Networking, VLSI and Signal Processing.
- [13] G.Shyam Kishore, "A Novel Full Adder with High Speed Low Area", 2nd National Conference on Information and Communication Technology (NCICT) 2011 Proceedings published in International Journal of Computer Applications® (IJCA).
- [14] Shubhajit Roy Chowdhury, Aritra Banerjee, Aniruddha Roy, Hiranmay Saha, "A high Speed 8 Transistor Full Adder Design using Novel 3 Transistor XOR Gates", International Journal of Electrical and Computer Engineering 3:12 2008.
- [15] Romana Yousuf and Najeeb-ud-din, "Synthesis of Carry Select Adder in 65 nm FPGA", IEEE.

[16] Shubin.V.V, “Analysis and Comparison of Ripple Carry Full Adders by Speed”, Micro/Nano Technologies and Electron Devices(EDM),2010, International Conference and Seminar on, pp.132-135,2010.

[17] Pudi. V, Sridhara., K, “Low Complexity Design of Ripple Carry and Brent Kung Addersin QCA”,Nanotechnology,IEEE transactions on,Vol.11,Issue.1,pp.105-119,2012.

[18] Jian-Fei Jiang; Zhi-Gang Mao; Wei-Feng He; Qin Wang, “A New Full Adder Design for Tree Structured Aritmetic Circuits”, Computer Engineering and Technology(ICCET),2010,2nd International Conference on,Vol.4,pp.V4-246-V4-249,2010.

Low Power Reversible Parallel Binary Adder/Subtractor

Rangaraju H G¹, Venugopal U², Muralidhara K N³, Raja K B ²

¹Department of Telecommunication Engineering, Bangalore Institute of Technology,
Bangalore, India

²Department of Electronics and Communication Engineering, University Visvesvaraya
College of Engineering, Bangalore, India

³Department of Electronics and Communication Engineering, P E S College of
Engineering, Mandya, Karnataka, India

ABSTRACT

In recent years, Reversible Logic is becoming more and more prominent technology having its applications in Low Power CMOS, Quantum Computing, Nanotechnology, and Optical Computing. Reversibility plays an important role when energy efficient computations are considered. In this paper, Reversible eight-bit Parallel Binary Adder/Subtractor with Design I, Design II and Design III are proposed. In all the three design approaches, the full Adder and Subtractors are realized in a single unit as compared to only full Subtractor in the existing design. The performance analysis is verified using number reversible gates, Garbage input/outputs and Quantum Cost. It is observed that Reversible eight-bit Parallel Binary Adder/Subtractor with Design III is efficient compared to Design I, Design II and existing design.

KEYWORDS

Reversible Logic, Garbage Input/output, Quantum Cost, Low Power, Reversible Parallel Binary Adder/Subtractor.

For More Details: <https://airconline.com/vlsics/V1N3/0910vlsics03.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol1.html>

REFERENCES

[1] C H Bennett, (1998) "Notes on the History of Reversible Computation", IBM Journal of Research and Development, vol. 32, pp. 16-23.

[2] R Landauer, (1961) "Irreversibility and Heat Generation in the Computational Process", IBM Journal of Research and Development, vol. 5, no. 3, pp. 183-191.

[3] C H Bennett, (1973) "Logical Reversibility of Computation", IBM Journal of Research and Development, vol. 17, no. 6, pp. 525-532.

- [4] T Toffoli, (1980) "Reversible Computing", Technical Memo MIT/LCS/TM-151, MIT Lab for Computer Science.
- [5] H Thapliyal and N Ranganathan, (2009) "Design of Efficient Reversible Binary Subtractors Based on a New Reversible Gate", IEEE Proceedings of the Computer Society Annual Symposium on VLSI, pp. 229-234.
- [6] H Thapliyal and N Ranganathan, (2010) "Design of Reversible Latches Optimized for Quantum Cost, Delay and Garbage Outputs", Proceedings of Twenty Third International Conference on VLSI Design, pp. 235-240.
- [7] Lihui Ni, Zhijin Guan, and Wenying Zhu, (2010) "A General Method of Constructing the Reversible FullAdder", Third International Symposium on Intelligent Information Technology and Security Informatics, pp.109-113.
- [8] Irina Hashmi and Hafiz Md. Hasan Babu, (2010) "An Efficient Design of a Reversible Barrel Shifter", Twenty Third International Conference on VLSI Design, pp. 93-98.
- [9] Robert Wille, Daniel Grobe, D Michael Miller, and Rolf Drechsler, (2009) "Equivalence Checking of Reversible Circuits", Thirty Ninth International Symposium on Multiple-Valued Logic, pp. 324-330.
- [10] Noor Muhammed Nayeem, Md. Adnan Hossain, Lafifa Jamal, and Hafiz Md. Hasan Babu, (2009) "Efficient Design of Shift Registers using Reversible Logic", International Conference on Signal Processing Systems, pp. 474-478.
- [11] Majid Mohammadi, Mohammad Eshghi, Majid Haghparast and Abbas Bahrololoom, (2008) "Design and Optimization of Reversible BCD Adder/Subtractor Circuit for Quantum and Nanotechnology Based Systems", World Applied Sciences Journal, vol. 4, no. 6, pp. 787-792.
- [12] Majid Mohammadi and Mohammad Eshghi, (2008) "Behavioral description of V and V+ gates to Design Quantum Logic Circuits", Fifth International Multi-Conference on Systems, Signals and Devices, pp. 1-6.
- [13] Rekha K James, Shahana T K, K Poullose Jacob, and Sreela Sasi, (2007) "A New Look at Reversible Logic Implementation of Decimal Adder", The International Symposium on System-On-Chip.
- [14] Himanshu Thapliyal and A P Vinod, (2006) "Transistor Realization of Reversible TSG Gate and Reversible Adder Architectures", Proceedings of IEEE Asia Pacific Conference on Circuits and Systems, pp. 418-421.
- [15] Himanshu Thapliyal and M B Srinivas, (2006) "Novel Design and Reversible Logic Synthesis of Multiplexer Based Full Adder and Multipliers", Forty Eight Midwest Symposium on Circuits and Systems, vol. 2, pp. 1593 – 1596.

- [16] Yvan Van Rentergem and Alexis De Vos, (2005) "Optimal Design of a Reversible Full Adder", International Journal of Unconventional Computing, vol. 1, pp. 339 – 355.
- [17] Mozammel H A Khan, (2004) "Quantum Realization of Ternary Adder Circuits", Proceedings of Third International Conference on Electrical and Computer Engineering, pp. 249-252.
- [18] Mozammel H A Khan, (2004) "Quantum Realization of Ternary Toffoli Gate", Proceedings of Third International Conference on Electrical and Computer Engineering, pp. 264-266.
- [19] Abhinav Agrawal and Niraj K Jha (2004) "Synthesis of Reversible Logic", Proceedings of the Design, Automation and Test in Europe Conference and Exhibition.
- [20] Pawel Kerntopf, (2002) "Synthesis of Multipurpose Reversible Logic Gates", Proceedings of the Euromicro Symposium on Digital System Design, pp. 259-266.

An Efficient FPGA Implementation of MRI Image Filtering and Tumour Characterization Using XILINX System Generator

Mrs. S. Allin Christe¹, Mr.M.Vignesh², Dr.A.Kandaswamy³

^{1,2} Department of Electronics & Communication Engineering , PSG College of Technology, Coimbatore,India

³ Department of Biomedical Engineering, PSG College of Technology, Coimbatore,India

ABSTRACT

This paper presents an efficient architecture for various image filtering algorithms and tumor characterization using Xilinx System Generator (XSG). This architecture offers an alternative through a graphical user interface that combines MATLAB, Simulink and XSG and explores important aspects concerned to hardware implementation. Performance of this architecture implemented in SPARTAN-3E Starter kit (XC3S500E-FG320) exceeds those of similar or greater resources architectures. The proposed architecture reduces the resources available on target device by 50%.

KEYWORDS

MRI, Matlab, Xilinx System Generator, FPGA, Edge Detection.

For More Details: <https://airconline.com/vlsics/V2N4/2411vlsics09.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol2.html>

REFERENCES

- [1] “Implementation and Evaluation of Image Processing Algorithms on Reconfigurable Architecture using C-based Hardware Descriptive Languages” Daggu Venkateshwar Rao, Shruti Patil, Naveen Anne Babu and V Muthukumar , International Journal of Theoretical and Applied Computer Sciences, Volume 1 Number 1 (2006) pp. 9–34
- [2] “Implementation of Image Processing Algorithms on FPGA hardware” by Anthony Edward Nelson ,MS thesis, May 2000.
- [3] “FPGA Implementation of an Efficient Partial Volume Interpolation for Medical Image Registration”,C. John Moses, Dr. D. Selvathi, S.Sajitha Rani, ICCCT-10, 2010 IEEE
- [4] “An Overview of MRI Brain Classification using FPGA Implementation” Dr Mohd Fauzi Bin Othman , Norarmalina Abdullah, Nur Aizudin Bin Ahmad Rusli,IEEE

Symposium on Industrial electronics & Applications (ISIEA) Oct 2010,Malaysia.

[5] “JPEG Image Compression Using an FPGA”, by James Rosenthal , MS thesis, Dec 2006.

[6] “FPGA Implementation of Subband Image Encoder Using Discrete Wavelet Transform”, by YounHong Kim , Kyong-il Jun, Kang-Hyeon Rhee, 1999 IEEE TENCON.

[7] “FPGA Implementation of Image Compression using bottom- up approach of Quad tree technique” by Satish K.Shah, Rakesh K.Soni,,Brijesh Shah, IETE Journal of research , Vol 57, Issue 2, Mar-Apr 2011.

[8] “Efficient FPGA Implementation of a WirelessCommunication System Using Bluetooth Connectivity”,Hasan Taha, Abdul N. Sazish, Afandi Ahmad, Mhd Saeed Sharif, and Abbes Amira, IEEE, 2010

[9] “Efficient hardware co-simulation of down converters for wireless communication systems”Rajesh Mehra and Swapna Devi, International journal of VLSI design & Communication Systems (VLSICS), Vol.1, No.2, June 2010

[10] “Modeling and Implementation of DSP FPGA Solutions”,Robert D. Turney, Chris Dick1, David B. Parlour, and James Hwang , Xilinx Inc

[11] “Performance Efficient FPGA Implementation of Parallel 2-D MRI Image Filtering Algorithms using Xilinx System Generator” by Sami Hasan, Alex Yakovlev and Said Boussakta, CSNDSP IEEE ,2010.

[12] Vehicle Image Edge Detection Algorithm Hardware Implementation on FPGA by ZhangShanshan and WangXiaohong, International Conference on Computer Application and System Modeling ,ICCA SM 2010.

[13] Xilinx System Generator User’s Guide,2010, downloadable from;[http:// www.Xilinx.com](http://www.Xilinx.com).

[14] “A Novel Architecture for Real Time Implementation of Edge Detectors on FPGA” by Sudeep K C and Dr. Jharna Majumdar, IJCSI International Journal of Computer Science Issues, Vol. 8, Issue 1, January 2011,pp 193-202.

[15] “Digital Image Processing” by Rafael C. Gonzalez , Richard E. Woods,2nd Edn,Prentice Hall,2002.

[16] “Optimal Operators in Digital Image Processing” by Scharr, Hanno, PhD thesis , 2000.

Comparative Performance Analysis of XORXNOR Function Based High-Speed CMOS Full Adder Circuits For Low Voltage VLSI Design

Subodh Wairya¹, Rajendra Kumar Nagaria² and Sudarshan Tiwari²

¹Department of Electronics Engineering, Institute of Engineering & Technology
(I.E.T), Lucknow, India, 226021

²Department of ECED, Motilal Nehru National Institute of Technology
(MNNIT), Allahabad, India, 211004

ABSTRACT

This paper presents comparative study of high-speed, low-power and low voltage full adder circuits. Our approach is based on XOR-XNOR design full adder circuits in a single unit. A low power and high performance 9T full adder cell using a design style called “XOR (3T)” is discussed. The designed circuit commands a high degree of regularity and symmetric higher density than the conventional CMOS design style as well as it lowers power consumption by using XOR (3T) logic circuits. Gate Diffusion Input (GDI) technique of low-power digital combinatorial circuit design is also described. This technique helps in reducing the power consumption and the area of digital circuits while maintaining low complexity of logic design. This paper analyses, evaluates and compares the performance of various adder circuits. Several simulations conducted using different voltage supplies, load capacitors and temperature variation demonstrate the superiority of the XOR (3T) based full adder designs in term of delay, power and power delay product (PDP) compared to the other full adder circuits. Simulation results illustrate the superiority of the designed adder circuits against the conventional CMOS, TG and Hybrid full adder circuits in terms of power, delay and power delay product (PDP).

KEYWORDS

Hybrid full adder, XOR-XNOR circuit, High Speed, Low Power, Very Large Scale Integrated (VLSI) Circuits.

For More Details: <https://airconline.com/vlsics/V3N2/3212vlsics19.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol3.html>

REFERENCES

- [1] John P. Uyemura, (2002) Introduction to VLSI Circuits and Systems, John Wiley & Sons.
- [2] Sung-Mo Kang, Y. Leblebici, (2005) CMOS Digital Integrated Circuits: Analysis and Design, Tata McGraw Hill, New York, NY, USA.

- [3] N. Weste and D. Harris, (2005) CMOS VLSI Design, Pearson Wesley.
- [4] N. Zhuang and H. Wu, (1992) "A new design of the CMOS full adder," IEEE Journal of Solid-State Circuits, Vol. 27, No. 5, pp. 840–844.
- [5] Y.Tsividis, (1996) Mixed Analog- Digital VLSI Devices and Technology, Singapore; McGraw Hill.
- [6] K.M. Chu and D. Puffrey, (1987) "A Comparison of CMOS Circuit Techniques Differential Cascode Voltage Switch Logic versus Conventional Logic," IEEE Journal of Solid-State Circuit, Vol. SC 22, No. 4, pp. 528- 532.
- [7] A. P. Chandrakasan, S. Sheng and R. W. Bordersen, (1992) "Low-power CMOS digital design," IEEE Journal of Solid-State Circuits, Vol. 27, No. 4, pp. 473- 484.
- [8] E. Abu-Sharma and M. Bayoumi, (1995) "A new cell for low power adders," in Proceeding of International Midwest Symposium Circuits System, pp. 1014-1017.
- [9] I. S. Abu-Khater, A. Bellaouar, and M.I. Elmasry, (1996) "Circuit techniques for CMOS low power high performance multipliers," IEEE Journal of Solid- State Circuits, Vol. 31, No. 10, pp. 1535-1546.
- [10] Uming Ko, Poras T. Balsara and Wai Lee, (1995) "Low-Power Design Techniques for HighPerformance CMOS adders," IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol. 3, No. 2, pp. 327-333.
- [11] A. Bellaouar and M. I. Elmasry, (1995) Low-Power Digital VLSI Design: Circuits and Systems, Kluwer Academic.
- [12] A. Parameswar, H. Hara and T. Sakurai, (1994) "A high speed, low power, swing restored passtransistor logic based multiply and accumulate circuit for multimedia applications," in Proceedings of IEEE Custom Integrated Circuits Conference, San Diego, USA, pp. 278–281.
- [13] A. Parameswar, H. Hara and T. Sakurai, (1996) "A swing restored pass-transistor logic-based multiply and accumulate circuit for multimedia applications," IEEE Journal of Solid-State Circuits, Vol. 31, No. 6, pp. 804–809.
- [14] K. Yano, Y. Sasaki, K. Rikino and K. Seki, (1996) "Top-down pass-transistor logic design," IEEE Journal of Solid-State Circuits, Vol. 31, No. 6, pp. 792–803.
- [15] Reto Zimmermann and Wolfgang Fichtner, (1997) "Low-power Logic Styles: CMOS versus pass transistor logic," IEEE Journal of Solid-State Circuits, Vol. 32, No. 7, pp. 1079-1090.

- [16] Ahmed M. Shams, and Magdy A. Bayoumi, (2000) "A Novel High- Performance CMOS 1-Bit FullAdder Cell," IEEE Transaction on Circuits and Systems. II, Vol. 47, No. 5, pp. 478–481.
- [17] Abdulkarim Al-Sheraidah, Yingtao Jiang, Yuke Wang and Edwin Sha, (2001) "A Novel Low Power Multiplexer-Based Full Adder," European Conference on Circuit Theory and Design, Espoo, Finland, pp. I329-I332.
- [18] D. Radhakrishnan, (2001) "Low-voltage low-power CMOS Full Adder," IEE Proceedings Circuit: Devices and Systems, Vol. 148, No. 1, pp. 19-24.
- [19] Fartash Vasefi and Z. Abid, (2005) "Low Power N-bit Adders and Multiplier using lowest number of Transistors 1-bit Adders," in Proceedings of IEEE Conference CCECE/CCGEI, 05 Saskatoon, pp.1731-1734.
- [20] Sumeer Goel, Ashok Kumar, Magdy A. Bayouni, (2006) "Design of Robust, Energy-Efficient Full Adders for Deep-Submicrometer Design Using Hybrid-CMOS Logic Style," IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol. 14, No. 12, pp. 1309-1321. International Journal of VLSI design & Communication Systems (VLSICS) Vol.3, No.2, April 2012 241
- [21] Ahmed M. Shams, Tarek K. Darwish, and Magdy A. Bayoumi, (2002) "Performance Analysis of Low-Power 1-Bit CMOS Full Adder Cells," IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol. 10, No. 1, pp. 20–29.
- [22] Mark Vesterbacka, (1999) "14-Transistor CMOS Full Adder with Full Voltage-Swing Nodes," in Proceedings of IEEE Workshop Signal Processing Systems, pp. 713-722.
- [23] R. Shalem, E. John and L. K. John, (1999) "Novel Low Power Energy Recovery Full Adder Cell," in Proceeding of 9th Great Lakes Symposium on VLSI (GLSVLSI'99), pp. 380–383.
- [24] Y. Jiang, A. Al-Sheraidah, Y. Wang, E. Shah, and J. Chung, (2004) "A Novel Multiplexer-Based Low Power Full Adder," IEEE Transactions on Circuits and Systems, Vol. 51, No. 7, pp. 345-348.
- [25] Hung Tien Bui, Yuke Wang and Yingtao Jiang, (2002) "Design and Analysis of Low-Power 10- Transistor Full Adders Using Novel XOR-XNOR Gates," IEEE Transactions on Circuits and Systems II: Analog and Digital Signal Processing, Vol. 49, No. 1, pp. 25-30.
- [26] S. Wairya, Himanshu Pandey, R. K. Nagaria and S. Tiwari, (2010) "Ultra Low Voltage High Speed 1- Bit CMOS Adder," in Proceedings of IEEE International Conference on Power, Control and Embedded System (ICPCES'10), India, pp. 1-6.

- [27] Chip-Hong Chang, Jiangmin Gu, Mingyan Zhang, (2005) "A Review of 0.18 μ m Full Adder Performances for Tree Structured Arithmetic Circuits," IEEE Transaction on Very Large Scale Integration (VLSI) Systems, Vol. 13, No. 6, pp. 686-694.
- [28] Sumeer Goel, Mohammed A. Elgamel, Magdy A. Bayoumi, Yasser Hanafy, (2006) "Design Methodologies for High-Performance Noise-Tolerant XOR-XNOR Circuits," IEEE Transactions on Circuits and Systems- I, Vol. 53, No. 4, pp. 867-878.
- [29] Jin-Fa-Lin, Yin-Tsung Hwang, Ming-Hwa Sheu, and Cheng-Che Ho, (2007) "A Novel High-Speed and Energy Efficient 10-Transistor Full Adder Design," IEEE Transaction on Circuits and Systems I, Vol. 54, No. 5, pp. 1050-1059.
- [30] S. Veeramachaneni, M. B. Srinivas, (2008) "New Improved 1-Bit Full Adder Cells," CCECE /CCGEI, May 5-7, 2008, Niagara Falls, Ontario, Canada, pp. 735-738,.
- [31] Arkadiy Morgenshtein, , Alexander Fish and Israel A. Wagner, (2002) "Gate-Diffusion Input (GDI): A Power Efficient Method for Digital Combinatorial Circuits," IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol. 10 No. 5, pp. 566 -581
- [32] Adarsh Kumar Agrawal, S. Wairya, R. K. Nagaria and S. Tiwari, (2009) "A New Mixed Gate Diffusion Input Full Adder Topology for High Speed Low Power Digital Circuits," World Applied Sciences Journal (WASJ) 7 (Special Issue of Computer & IT): pp. 138-144.
- [33] Mohammad Hossein Moaiyeri and Reza Faghieh Mirzaee, (2009) "Two New Low-Power and HighPerformance Full Adders," Journal of Computers, Vol. 4, No. 2, pp. 119-126.
- [34] MA Elgmal, S. Goel and M.A. Bayoumi, (2003) "Noise Tolerant Low Voltage XOR-XNOR for Fast Arithmetic," in Proceeding of IEEE Great Lakes Symposium on VLSI (GLSVLSI' 03), 2003, Wasting D.C., pp. 285-288.
- [35] Shiv Shankar Mishra, S. Wairya, R.K. Nagaria and S. Tiwari, (2009) "New Design Methodologies for High Speed Low Power XOR-XNOR Circuits," Journal of World Academy Science, Engineering and Technology (WASET), Vol. 55, No. 35, pp. 200-206.
- [36] S. Wairya, R. K. Nagaria and S. Tiwari, (2010) "A Novel CMOS Full Adder Topology for Low Voltage VLSI Applications," in Proceeding of International Conference on Emerging Trends in Signal Processing & VLSI Design (SPVL'10)', Hyderabad, India, pp. 1142-1146.
- [37] Shubhajit Roy Chowdhury, Aritra Banerjee, Aniruddha Roy and H. Saha, (2008) "A high Speed 8 Transistor Full Adder Design using Novel 3 Transistor XOR Gates," International Journal of Electronics, Circuits and Systems, WASET Fall, Vol. 2, No. 4, pp. 217-223.

- [38] Mariano Aguirre-Hernandez and Monico Linares-Aranda, (2011) "CMOS Full Adders for EnergyEfficient Arithmetic Application," IEEE Transactions on Very Large Scale Integration (VLSI) System, Vol. 19, No. 4, pp. 718-721.
- [39] M. Hosseinghadiry, H. Mohammadi, M. Nadisenejani, (2009) "Two New Low Power High Performance Full Adders with Minimum Gates," International Journal of Electronics, Circuits and Systems, Vol. 3, No. 2, pp. 124-131.
- [40] Subodh Wairya, Rajendra Kumar Nagaria and Sudarshan Tiwari, (2011) "New Design Methodologies for High-Speed Low-Voltage 1 Bit CMOS Full Adder Circuits," Journal of Computer Technology and Application, Vol. 2, No. 3, pp. 190-198.
- [41] Subodh Wairya, Rajendra Kumar Nagaria and Sudarshan Tiwari, (2011) "New Design Methodologies for High Speed Mixed Mode Full Adder Circuits," International Journal of VLSI and Communication Systems, Vol. 2, No. 2, pp. 78-98.
- [42] Subodh Wairya , Garima Singh, Vishant, R. K. Nagaria and S. Tiwari (2011), "Design Analysis of XOR (4T) based Low Voltage CMOS Full Adder Cell," In Proceeding of IEEE International Conference on Current Trends In Technology (NUICONE'11), Ahmedabad, India pp. 1-7.
- [43] Subodh Wairya, Rajendra Kumar Nagaria and Sudarshan Tiwari, (2012) "Performance Analysis of High Speed Hybrid CMOS Full Adder Circuits for Low Voltage VLSI Design," VLSI Design, Vol. 2012, Article ID 173079, 18 pages.

Single bit full adder design using 8 transistors with novel 3 transistors XNOR gate

Manoj Kumar¹, Sandeep K. Arya¹ and Sujata Pandey²

¹Department of Electronics & Communication Engineering Guru Jambheshwar
University of Science & Technology, Hisar, 125 001, India

²Amity University, Noida, 201303, India

ABSTRACT

In present work a new XNOR gate using three transistors has been presented, which shows power dissipation of 550.7272 μ W in 0.35 μ m technology with supply voltage of 3.3V. Minimum level for high output of 2.05V and maximum level for low output of 0.084V have been obtained. A single bit full adder using eight transistors has been designed using proposed XNOR cell, which shows power dissipation of 581.542 μ W. Minimum level for high output of 1.97V and maximum level for low output of 0.24V is obtained for sum output signal. For carry signal maximum level for low output of 0.32V and minimum level for high output of 3.2V have been achieved. Simulations have been performed by using SPICE based on TSMC 0.35 μ m CMOS technology. Power consumption of proposed XNOR gate and full adder has been compared with earlier reported circuits and proposed circuit's shows better performance in terms of power consumption and transistor count.

KEYWORDS

CMOS, exclusive-OR (XOR), exclusive-NOR (XNOR), full adder, low power, pass transistor logic.

For More Details: <https://airconline.com/vlsics/V2N4/2411vlsics05.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol2.html>

REFERENCES

- [1] Y. Leblebici, S.M. Kang, CMOS Digital Integrated Circuits, Singapore: Mc Graw Hill, 2nd edition, 1999.
- [2] A. M. Shams and M. Bayoumi, "A novel high-performance CMOS1-bit full adder cell," IEEE Transaction on Circuits Systems II, Analog Digital Signal Process, vol. 47, no. 5, pp. 478–481, May 2000.
- [3] Ahmed M. Shams and Magdy A, "A structured approach for designing low power adders," Conference Record of the Thirty-First Asilomar Conference on Signals, Systems & Computers, vol.1, pp.757-761, Nov. 1997.

- [4] R. Zimmermann, and W. Fichtner, "Low-power logic styles: CMOS versus pass-transistor logic," IEEE J. Solid State Circuits, vol. 32, no. 7, pp. 1079-1090, Jul. 1997.
- [5] N. Weste and K. Eshraghian, Principles of CMOS VLSI Design, A System Perspective, AddisonWesley, 1993.
- [6] N. Zhuang and H. Wu, "A new design of the CMOS full adder," IEEE J. Solid-State Circuits, vol. 27, no. 5, pp. 840–844, May 1992.
- [7] Yingtao Jiang Al-Sheraidah, A. Yuke Wang Sha, E. and Jin-Gyun Chung, "A novel multiplexerbased low-power full adder," IEEE Transactions on Circuits and Systems: Express Briefs, vol. 51, no. 7, pp.345-348, Jul. 2004.
- [8] R. Shalem, E. John, and L. K. John, "A novel low-power energy recovery full adder cell," in Proc. Great Lakes Symposium on VLSI, pp. 380–383, Feb. 1999.
- [9] H. T. Bui, Y. Wang, and Y. Jiang, "Design and analysis of low-power 10-transistor full adders using XOR-XNOR gates," IEEE Transactions Circuits Systems II, Analog Digital Signal Process, vol. 49, no. 1, pp. 25– 30, Jan. 2002.
- [10] S. Goel. A. Kumar, M. A. Bayoumi, "Design of robust, energy –efficient full adders for deep sub micrometer design using hybrid-CMOS logic style," IEEE Transactions on Very Large Scale Integration (VLSI) Systems, vol.14, no.12, pp.1309-1321, Dec. 2006.
- [11] Zhang, M., J. Gu and C.H. Chang, "A novel hybrid pass logic with static CMOS output drive fulladder cell," IEEE Int. Symposium on Circuits Systems, vol. 5, pp. 317-320, May 2003.
- [12] Chiou-Kou Tung, Yu-Cherng Hung, Shao-Hui Shieh, and Guo-Shing Huang, " A Low-Power HighSpeed Hybrid CMOS Full Adder for Embedded System," IEEE conference on Design and Diagnostics of Electronic Circuits and Systems, pp.1-4, 2007.
- [13] D. Radhakrishnan, "Low-voltage low-power CMOS full adder," in Proc. IEE Circuits Devices System, vol. 148, pp. 19-24, Feb. 2001.
- [14] J.-M. Wang, S.-C. Fang, and W.-S. Feng, "New efficient designs for XOR and XNOR functions on the transistor level," IEEE J. Solid-State Circuits, vol. 29, no. 7, pp. 780–786, Jul. 1994.
- [15] H. T. Bui, A. K. Al-Sheraidah, and Y.Wang, "New 4-transistors XOR and XNOR designs," in Proc. 2nd IEEE Asia Pacific Conference, ASIC, pp. 25–28, Aug. 2000.
- [16] H.T. Bui, Y. Wang, Y. Jiang , "Design and analysis of 10-transistor full adders using novel XOR–XNOR gates," in Proc. 5th International Conference on Signal Process., vol. 1, pp. 619–622, Aug. 21–25, 2000.International Journal of VLSI design & Communication Systems (VLSICS) Vol.2, No.4, December 2011

- [17] Jin-Fa Lin, Y.T. Hwang, M.H.Sheu and C.C.Ho, "A Novel High-Speed and Energy Efficient 10-Transistor Full Adder Design," IEEE Transactions on Circuits and Systems, vol. 54, no. 5 pp.1050-1059, May 2007.
- [18] Sung-Chuan Fang, Jyh-Ming Wang, and Wu-Shiung Feng, "A new direct design for three-input XOR function on the transistor level," IEEE Trans. Circuits System I: Fundamental theory and Applications, vol. 43, no. 4, Apr. 1996.
- [19] A. M. Shams, T. K. Darwish, and M. A. Bayoumi, "Performance analysis of low-power 1-bit CMOS full adder cells," IEEE Trans. Very Large Scale Integration (VLSI) Systems, vol. 10, no. 1, pp. 20–29, Feb. 2002.
- [20] S. Goel, M. E. Elgamel, M. A. Bayouni, and Y. Hanafy, "Design methodologies for highperformance noise-tolerant XOR-XNOR circuits," IEEE Trans. Circuits and System. I, vol. 53, no. 4, Apr. 2006.
- [21] Shiv Shankar Mishra, S. Wairya, R.K. Nagaria and S. Tiwari, "New design methodologies for high speed low power XOR-XNOR circuits," World Academy of Science, Engineering and Technology, vol.55, pp.200-206, 2009.
- [22] Manoj Kumar, Sandeep K. Arya and Sujata Pandey, "Low power CMOS full adder design with body biasing approach," Journal of Integrated Circuits and Systems, Brazil, vol. 6, no.1, pp.75-80, March 2011.
- [23] Manoj Kumar, Sujata Pandey and Sandeep K. Arya, "Design of CMOS Energy Efficient Single Bit Full Adder," Book Chapter of Communications in Computer and Information Science, SpringerVerlag Berlin Heidelberg, CCIS 169, pp. 159-168, Jul. 2011.
- [24] Y.Tsividis, Mixed Analog-Digital VLSI devices and Technology, Singapore: McGraw Hill, 1996.
- [25] Phillip E. Allen and Douglas R. Holberg, CMOS analog circuit design, Oxford University Press, 2009.
- [26] Behzad Razavi, Design of Analog CMOS Integrated Circuits, Tata McGraw Hill, 2002.

Arithmetic Operations in Multi-Valued Logic

Vasundara Patel k s¹, k s gurumurthy²

¹Dept of ECE, BMSCE, Vishweshwaraiah Technological University, Bangalore

²Dept of E&C, UVCE, Bangalore

ABSTRACT

This paper presents arithmetic operations like addition, subtraction and multiplications in Modulo-4 arithmetic, and also addition, multiplication in Galois field, using multi-valued logic (MVL). Quaternary to binary and binary to quaternary converters are designed using down literal circuits. Negation in modular arithmetic is designed with only one gate. Logic design of each operation is achieved by reducing the terms using Karnaugh diagrams, keeping minimum number of gates and depth of net in to consideration. Quaternary multiplier circuit is proposed to achieve required optimization. Simulation result of each operation is shown separately using Hspice.

KEYWORDS

Multiple-valued logic, Quaternary logic, Modulo-n addition and multiplication, Galois addition and multiplication.

For More Details: <https://airconline.com/vlsics/V1N1/0310vlsics3.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol1.html>

REFERENCES

- [1] K. C. Smith, "The prospects for multi-valued logic: A technology and applications view," IEEE Trans. Computers, vol. C-30, no. 9, pp. 619–634, Sep. 1981.
- [2] Kawahito, S. Kameyama, "A 32 X 32 bit Multiplier using Multiple-valued MOS Current Mode Circuit", Journal of Solid-State Circuits, IEEE, Vol.1, pp. 124 - 132 Feb.1988.
- [3] M. Thodis , D. Soudris , J.-M. Fernandez, and A. Thanailakis, "The circuit design of multiplevalued logic voltage-mode adders ", Proceedings of the 2001 IEEE International Symposium on Circuits and Systems (ISCAS 2001), May 6-9, 2001, Sydney, Australia, vol. IV, pp.162-165.
- [4] Ricardo Cunha Goncalves da Silva, "A low power high performance CMOS voltage mode quaternary full adder", IFIP Int. Conference on VLSI, pp.187-191, IFIP Oct. 2006.

[5] Hirokatsu Shirahama and Takahiro Hanyu, "Design of High-Performance Quaternary Adders Based on Output-Generator Sharing", Proceedings of the 38th International Symposium on Multiple Valued Logic P: 8-13, 2008.

[6] Shulin, Daniel J, Costello, "Error control coding", Pearson Prentice Hall, second edition.

[7] Nabil Abu-Khader, Pepe Siy, "Computation in Galois field using Multiple-valued logic", NOFIPS, North American Fuzzy Information Processing System, 2005.

[8] Hsu, I. S.; Truong, T. K.; Reed, I. S., "A VLSI architecture for Performing Finite field Arithmetic with reduced Table Look up", The Telecommunications and Data Acquisition Report, pp. 143 - 154 (SEE N87-11024 02-32) April June 1986.

[9] Kovac, M. Ranganathan, N. Varanasi, "M SIGMA: a VLSI systolic array implementation of a Galois field $GF(2^m)$ based multiplication and division algorithm", IEEE Transactions on Very Large Scale Integration (VLSI) Systems, Vol.1, pp. 22-30, March 1993.

[10] P Kitsos et. Al, "An efficient reconfigurable multiplier architecture for Galois field $GF(2^m)$ ", Micro electronics journal vol.34, pp. 975-980, 2003.

[11] Nabil Abu-Khader, Pepe Siy, "Multiple-Valued Logic Approach for a Systolic² AB Circuit in Galois Field". 35th International Symposium on Multiple-Valued Logic (ISMVL'05), May 19-May 21, 2005.

[12] Jun-Cheol Jeon, Kee-Won Kim and Kee-Young Yoo, "A novel approach for bit-serial AB² multiplication in finite fields $GF(2^m)$ ", Computers & Mathematics with Applications, Volume 51, Issues 6-7, Pages 1103-1112, March-April 2006.

[13] Che-wun chiou et-al, "Efficient VLSI implementation for Montgomery multiplication in Galois field $GF(2)$ ", Tamkang Journal of science and Engg, Vol9, No4, pp 365-372 (2006)

[14] Nabil Abu-Khader, Pepe Siy, "Inversion and division in Galois field using multiple valued logic". Proceedings of the 37th international conference on multiple valued logic (ISMVL 07), pp.16 May 13-May 16, 2007.

[15] Bjor Abrahamsson, "Architecture for Multiplication in Galois rings", June 2004.

[16] Ricardo Cunha, "quaternary lookup tables using voltage mode CMOS logic design", ISMVL 2007. 37th International Symposium on Multiple-Valued Logic, pp.56-56, 2007, 13-16 May, 2007.

[17] Nabi Abu-Khader, Pepe Siy, "Systolic product sum circuit for $GF((2^2)^m)$ using neuron MOSFET", INTEGRATION, The VLSI journal, vol. 39 pp.29 - 47., year 2005.

Design of Reversible Sequential Circuit Using Reversible Logic Synthesis

Md. Belayet Ali¹, Md. Mosharof Hossin¹ and Md. Eneyat Ullah¹

¹Dept of ECE, BMSCE, Vishweshwaraiah Technological University, Bangalore

ABSTRACT

Reversible logic is one of the most vital issue at present time and it has different areas for its application, those are low power CMOS, quantum computing, nanotechnology, cryptography, optical computing, DNA computing, digital signal processing (DSP), quantum dot cellular automata, communication, computer graphics. It is not possible to realize quantum computing without implementation of reversible logic. The main purposes of designing reversible logic are to decrease quantum cost, depth of the circuits and the number of garbage outputs. In this paper, we have proposed a new reversible gate. And we have designed RS flip flop and D flip flop by using our proposed gate and Peres gate. The proposed designs are better than the existing proposed ones in terms of number of reversible gates and garbage outputs. So, this realization is more efficient and less costly than other realizations.

KEYWORDS

Reversible logic, Reversible gate, Power dissipation, Flip-Flop, Garbage, BME gate.

For More Details: <https://airconline.com/vlsics/V2N4/2411vlsics04.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol2.html>

REFERENCES

- [1] R. Landauer, "Irreversibility and heat generation in the computing process," IBM J. Research & Development, vol. 5, no. 3, pp. 183–191, July 1961.
- [2] C. Bennett, "Logical reversibility of computation," IBM J. Research & Development, vol. 17, no. 6, pp. 525–532, Nov. 1973.
- [3] S. Younis and T. Knight, "Asymptotically Zero Energy Split-Level Charge Recovery Logic," Workshop on Low Power Design, 1994.
- [4] T. Toffoli, Automata, Languages and Programming. Springer Verlag, 1980, chapter: Reversible Computing, pp. 632–644.
- [5] Babu HMH, Islam MR, Chowdhury AR, Chowdhury SMA. "Synthesis of full-adder circuit using reversible logic", 17th International Conference on VLSI Design 2004, 757-60.

- [6] T. Toffoli., “Reversible Computing”, Tech memo MIT/LCS/TM-151, MIT Lab for Computer Science (1980).
- [7] E. Fredkin and T. Toffoli, “Conservative logic,” Int’l J. Theoretical Physics, Vol. 21, pp.219-253, 1982.
- [8] H.R.Bhagyalakshmi and M.K.Venkatesha, “Optimized reversible BCD adder using new reversible logic gates”, Journal of Computing, Volume 2, Issue 2, February 2010, ISSN 2151-9617 arXiv:1002.3994v1.
- [9] M. Haghparast, K. Navi, ”A Novel Reversible BCD Adder For Nanotechnology Based Systems”, American Journal of Applied Sciences 5 (3): 282-288, 2008, ISSN 1546-9239.
- [10] Ashis Kumer Biswas, Md. Mahmudul Hasan, Moshaddek Hasan, Ahsan Raja Chowdhury and Hafiz Md. Hasan Babu. “A Novel Approach to Design BCD Adder and Carry Skip BCD Adder”. 21st International Conference on VLSI Design, 1063-9667/08 \$25.00 © 2008 IEEE DOI 10.1109/VLSI.2008.37.
- [11] H.R.Bhagyalakshmi, M.K.venkatesha. “An improved design of a multiplier using reversible logic gates”. International Journal of Engineering Science and Technology, Vol. 2(8), 2010, 3838-3845.
- [12] Abu Sadat Md. Sayem, Masashi Ueda.” Optimization of reversible sequential circuits”. Journal of Computing, Volume 2, Issue 6, June 2010, ISSN 2151-9617.
- [13] R. Feynman, “Quantum Mechanical Computers,” Optics News, Vol.11, pp. 11–20, 1985.
- [14] B. Parhami, “Fault Tolerant Reversible Circuits” Proc. 40th Asilomar Conf. Signals, Systems, and Computers, Pacific Grove, CA, Oct.2006.
- [15] A. Peres, “Reversible Logic and Quantum Computers”, Physical review A, 32:3266-3276, 1985.
- [16] W. N. N. Hung, X. Song, G. Yang, J. Yang and M. Perkowski, “Quantum Logic Synthesis by Symbolic Reachability Analysis”, Proc. 41st annual conference on Design automation DAC, pp.838-841, January 2004.
- [17] Ashis Kumer Biswas, Lafifa Jamal, M. A. Mottalib1, Hafiz Md. Hasan Babu.” Design of a Reversible Parallel Loading Shift Register ”. Dhaka Univ. J. Eng & Tech. Vol 1(2) 1-5, 2011.
- [18] Himanshu Thapliyal, M.B.Srinivas, and M.Zwolinski, "A Beginning in the Reversible Logic Synthesis of Sequential Circuits “, MAPLD Conference (NASA office of Logic Design), vol.8 2005.

- [19] J.Smoline and David P.DiVincenzo, “Five two-qubit gates are sufficient to implement the quantum fredkin gate”, Physics Review A, vol. 53, no.4, pp. 2855-2856, 1996.
- [20] Yang G., Song X, Hung WNN, and Marek Perkowski, “Bi-direction Synthesis for Reversible circuits”, IEEE Computer Society Annua; Symposium on VLSI New Frontiers in VLSI Design, 2007.
- [21] D. Maslov and G.W. Dueck, “Reversible cascades with Minimal Garbage”, IEEE Transactions on CAD, vol. 23(11), pp. 1497-1509, November 2004.
- [22] Richard P.Feynman, “Quantum mechanical computers”, Foundations of Physics, vol.16, no. 6, pp.507-531,1986.
- [23] D. Maslov, G.W. Dueck, D.M. Miller, “Toffoli Network Synthesis with templates”, IEEE Transactions on Computer Aided Design of Integrated Circuits and Systems, Vol.24, Issue 6, June 2005, pp:807-817

Analog VLSI Implementation of Neural Network Architecture for Signal Processing

Neeraj Chasta¹, Sarita Chouhan² and Yogesh Kumar³

¹Department of Electronics and Communication, Mewar University, Chittorgarh,
Rajasthan, India

²Department of Electronics and Communication, MLVTEC, Bhilwara, Rajasthan, India
2Department

³Electronics and Communication, MLVTEC Bhilwara, Rajasthan, India

ABSTRACT

With the advent of new technologies and advancement in medical science we are trying to process the information artificially as our biological system performs inside our body. Artificial intelligence through a biological word is realized based on mathematical equations and artificial neurons. Our main focus is on the implementation of Neural Network Architecture (NNA) with on a chip learning in analog VLSI for generic signal processing applications. In the proposed paper analog components like Gilbert Cell Multiplier (GCM), Neuron activation Function (NAF) are used to implement artificial NNA. The analog components used are comprises of multipliers and adders' along with the tan-sigmoid function circuit using MOS transistor in subthreshold region. This neural architecture is trained using Back propagation (BP) algorithm in analog domain with new techniques of weight storage. Layout design and verification of the proposed design is carried out using Tanner EDA 14.1 tool and synopsys Tspice. The technology used in designing the layouts is MOSIS/HP 0.5u SCN3M, Tight Metal.

KEYWORDS

Neural Network Architecture, Back Propagation Algorithm.

For More Details: <https://airconline.com/vlsics/V3N2/3212vlsics20.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol3.html>

REFERENCES

[1] Cyril Prasanna Raj P & S.L. Pinnae "DESIGN AND ANALOG VLSI IMPLEMENTATION OF NEURAL NETWORK ARCHITECTURE FOR SIGNAL PROCESSING" European Journal of Scientific Research ISSN 1450-216X Vol.27No.2 (2009), pp.199-216

[2] George Papadourakis "INTRODUCTION TO NEURAL NETWORKS" (2009)

- [3] Anita Wasilewska "NEURAL NETWORKS" State University of New York at Stony Brook.
- [4] Ranjeet Ranade & Sanjay Bhandari & A.N. Chandorkar "VLSI Implementation of Artificial Neural Digital Multiplier and Adder" pp.318-319
- [5] Rafid Ahmed Khalil & Sa'ad Ahmed Al-Kazzaz "Digital Hardware Implementation of Artificial Neurons Models Using FPGA" pp.12-24
- [6] Bose N.K., Liang P., Neural Network Fundamentals With graphs, algorithms and Application, Tata McGraw hill, New Delhi, 2002, ISBN0-07-463529-8.
- [7] Razavi Behzad, Design of Analog CMOS Integrated Circuits, Tata McGraw hill, New Delhi , 2002, ISBN0-07-052903-5.
- [8] Roy Ludvig Sigvartsen, An Analog Neural Network With On-Chip Learning Thesis Department of informatics, University of Oslo, 1994
- [9] Isik Aybayetal , Classification of Neural Network Hardware, Neural Network World ,IDG Co., Vol6 No1, 1996, pp.11-29 ,
- [10] Vincent F. Koosh Analog Computation and Learning in VLSI PhD thesis California institute of technology, Pasadena, California.2001.
- [11] E. Vittoz, et al.," The design of high performance analog circuits on digital CMOS chips," IEEE J. Solid State Circuit 20, 1985, pp.657-665
- [12] S. Orcioni G. Biagetti, M. Conti, "A mixed signal fuzzy controller using current model circuits, " Analog Integrated Circuits Process. 38, 2004 , pp.215-231.
- [13] F. Djeflal et al., "Design and Simulation of Nanoelectronic DG MOSFET Current Source using Artificial Neural Networks," Materials Science and Engineering C, vol. 27, 2007, pp. 1111-1116
- [14] H. Ben Hommounda et al., "Neural Based Models Of Semiconductor Devices for Spice Simulator," American J. of Applied Science, vol. 5, 2008, pp. 385-391
- [15] Arne Heittmann, "An Analog VLSI Pulsed Neural Network for Image Segmentation using Adaptive Connection Weights" Dresden University of Technology, Department of Electrical Engineering and Information Technology,Dresden, Germany, 2000
- [16] Wai-Chi Fang et al, "A VLSI Neural Processor for Image Data Compression using Self-Organisation Networks" IEEE Transactions on Neural Networks, Vol. 3, No. 3, May 1992, pp. 506-517
- [17] R. Rojas, Neural Networks, Springer-Verlag, Berlin, 1996

- [18] D. Nguyen a and B. Wid row, Improving the learning speed of 2-layer neural network by choosing initial values of the adaptive weights, IEEE First International Joint Conference on Neural Networks ,3, 21–26, (1990).
- [19] R.A. Jacobs, Increased rates of convergence through learning rate adaptat ion , Neural Networks , 1 ,295–307, (1988).
- [20] T. P. Vogl, J. K. Man gis, J.K. Rigler, W. T. Z ink and D .L. Alkon, Accelerating the convergence of the back-propagation method , Biological Cyberne tics, 59 , 257–263,(1988).

Cell Stability Analysis of Conventional 6T Dynamic 8T SRAM Cell in 45NM Technology

K. Dhanumjaya¹, M. Sudha², Dr.MN.Giri Prasad³, Dr.K.Padmaraju⁴

¹Research Scholar, Jawaharlal Nehru Technological University, Anantapur, AP, INDIA

²PG Student, Jawaharlal Nehru Technological University, Anantapur, AP, INDIA

³Professor, Jawaharlal Nehru Technological University, Anantapur, AP, INDIA

⁴Professor, Jawaharlal Nehru Technological University, Kakinada, AP, INDIA

ABSTRACT

A SRAM cell must meet requirements for operation in submicron/nano ranges. The scaling of CMOS technology has significant impact on SRAM cell -- random fluctuation of electrical characteristics and substantial leakage current. In this paper we present dynamic column based power supply 8T SRAM cell and comparing the proposed SRAM cell with respect to conventional SRAM 6T in various aspects. To verify read stability and write ability analysis we use N-curve metric. Simulation results affirmed that proposed 8T SRAM cell achieved improved read stability, read current, and leakage current in 45nm Technology comparing with conventional 6T SRAM using cadence virtuoso tool.

KEYWORDS

SRAM, Leakage Current, N-curve, Read stability, Write-ability, Cadence, Virtuoso, 45nm Technology.

For More Details: <https://aircconline.com/vlsics/V3N2/3212vlsics04.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol3.html>

REFERENCES

- [1] V. Gupta and M. Anis, "Statistical design of the 6T SRAM bit cell," IEEE Trans. Circuits Syst. I, Reg. Papers, vol. 57, no. 1, pp. 93–104, Mar. 2010.
- [2] C. Molina, C. Aliagas, M. Garcia, A. Gonzcalezo, J. Tubellao. Non Redundant Data Cache. In ISLPED, pages 274–277, August 2003.
- [3] E. Grossar et al., "Read stability and write-ability analysis of SRAM cells for nanometer technologies," IEEE J. Solid-State Circuits, vol.41, no. 11, pp. 2577–2588, Nov. 2006.
- [4] Do Anh-Tuan, Jeremy Yung Shern Low, Joshua Yung Lih Low, Zhi-Hui Kong, Xiaoliang Tan, and Kiat-Seng Yeo,"An 8T Differential SRAM With Improved Noise Margin for Bit-Interleaving in 65 nm CMOS" IEEE Transnctions on circuits and

systems—I :regular papers, Vol. 58, No. 6, june 2011.

[5] Jan M. Rabaey, Anantha Chandrakasan and Borivoje Nikolic, "Digital Integrated Circuits", ISBN 81-7808-991-2, Pearson Education, 2003.

[6] Antonio J. Lopez Martin "CADENCE DESIGN ENVIRONMENT" Klipsch School of Electrical and Computer Engineering, New Mexico State University, October 2002.

[7] Neil H.E. Weste, David Harris and Ayan Banerjee, "CMOS VLSI Design, a circuits and systems perspective", ISBN: 0321149017/9780321149015 Third edition, Pearson Education, 2005.

[8] C. Ik Joon et al., "A 32 kb 10T subthreshold SRAM array with bitinterleaving and differential read scheme in 90 nm CMOS," IEEE J. Solid-State Circuits, vol. 44, no. 2, pp. 650–658, Feb. 2009.

[9] E. Seevinck et al., "Static-noise margin analysis of MOS SRAM cells," IEEE J. Solid-State Circuits, vol. SSC-22, no. 5, pp. 748–754, Oct. 1987.

Wishbone Bus Architecture - A Survey and Comparison

Mohandeep Sharma¹ and Dilip Kumar²

¹Department of VLSI Design, Center for Development of Advanced Computing,
Mohali, India

²ACS - Division, Center for Development of Advanced Computing, Mohali, India

ABSTRACT

The performance of an on-chip interconnection architecture used for communication between IP cores depends on the efficiency of its bus architecture. Any bus architecture having advantages of faster bus clock speed, extra data transfer cycle, improved bus width and throughput is highly desirable for a low cost, reduced time-to-market and efficient System-on-Chip (SoC). This paper presents a survey of WISHBONE bus architecture and its comparison with three other on-chip bus architectures viz. Advanced Microcontroller Bus Architecture (AMBA) by ARM, CoreConnect by IBM and Avalon by Altera. The WISHBONE Bus Architecture by Silicore Corporation appears to be gaining an upper edge over the other three bus architecture types because of its special performance parameters like the use of flexible arbitration scheme and additional data transfer cycle (Read-Modify-Write cycle). Moreover, its IP Cores are available free for use requiring neither any registration nor any agreement or license.

KEYWORDS

SoC buses, WISHBONE Bus, WISHBONE Interface.

For More Details: <https://airconline.com/vlsics/V3N2/3212vlsics10.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol3.html>

REFERENCES

- [1] Milica Mitić and Mile Stojčev, “A Survey of Three System-on-Chip Buses: AMBA, CoreConnect and Wishbone,” ICEST 2006.
- [2] Bernini L. and De Micheli G., Networks on Chips. A New Paradigm for Component-based MpSoC Design, chapter 3 in Jerraya A.A. and Wolf W., (Eds.), Multiprocessor Systems-on-Chips, Elsevier, Amsterdam, pp. 49–80, 2005.
- [3] R.UMA, Vidya Vijayan, M. Mohanapriya, Sharon Paul, “Area, Delay and Power Comparison of Adder Topologies,” International Journal of VLSI design & Communication Systems (VLSICS) Vol.3, No.1, p. 161, February 2012.

- [4] Ho W.H. and Pinkston T.M., "A Design Methodology for Efficient Application-specific on-chip interconnects," IEEE Trans. Parallel Distributed System, 17(2), pp. 174-179, February 2006.
- [5] Kyeong Keol Ryu, Shin, and Vincent J. Mooney, "A Comparison of Five Different Multi processor SoC Bus Architectures," Digital Systems Design: Proceedings. Euro micro Symposium, Warsaw, Poland, p.209, Sept. 2001.
- [6] Richard Herveille, WISHBONE System-on-Chip (SoC) Interconnection Architecture for Portable IP Cores, Open Cores Organization, rev. version: B4, 2010.
- [7] ARM, "AMBA Specification (Rev. 2.0), 1999. Available online at: <http://www.arm.com>.
- [8] IBM Corp., USA," CoreConnect bus Architecture," 1999. [Online] www.ibm.com/chips/products/coreconnect/
- [9] Altera Avalon, Avalon bus specification: Reference Manual. Altera Corporation, July, 2003 Available online at: <http://www.altera.com>
- [10] Richard Herveille, WISHBONE System-on-Chip (SoC) Interconnection Architecture for Portable IP Cores, rev. version: B4, 2010. By Open Cores Organization, p.7, 2010. www.opencores.org
- [11] Muhammad Mun'im Ahmad Zabidi, Selvakumar Rajagopal, "Open Source Microprocessor and OnChip-Bus for System-on-Chip," Advances in Embedded Systems, Eds. Muhammad Mun'im Ahmad Zabidi & Muhammad Nadzir Marsono and Penerbit UTM Press: Malaysia, p.5, 2008.
- [12] Silicore Corporation, "WISHBONE Frequently Asked Questions (FAQ)," updated: March 18, 02, p.1, March 2002 [Online] www.pldworld.com/hdl/2/ip/silicore.net/wishfaq.htm.
- [13] Richard Herveille, "Combining WISHBONE Interfaces Signals: Application note," Rev. 0.2 Preliminary, p. 2, April 18, 2001. Available online at: http://cdn.opencores.org/downloads/appnote_01.pdf
- [14] WISHBONE System-on-Chip (SoC) Interconnection Architecture for Portable IP Cores, rev. version: B4, p.92, 2010.
- [15] Balal Ahmad, "Communication Centric Platforms for Future High Data Intensive Applications," Ph.D. Thesis: The University of Edinburgh, p.25, March 2009.
- [16] M. Mitic et al. "An Overview of On-Chip Buses", FACTA Universitatis Series: Electronics and Energetics, 19(3), pp. 405-428, December 2006. Also in Embedded Systems Handbook, Digital Systems and Applications, Z.Oklobdzija, CRC Press, 2008.

- [17] M. K. Vernon, and U. Manber, "Distributed round-robin and first-come first-serve protocols and their applications to multiprocessor bus arbitration," SIGARCH, ISCA 1988
- [18] W. J. Dally and B. Towel, Principles and Practices of Interconnection Networks, Amsterdam: Elsevier, 2004.
- [19] Anurag Shrivastava, G.S. Tomar, and Ashutosh Kumar Singh, "Performance Comparison of AMBA Bus-Based System-On-Chip Communication Protocol," International Conference on Communication Systems and Network Technologies, IEEE Computer Society, p. 449, 2011.
- [20] ARM, "AMBA Multi-Layer AHB Overview," in AMBA 3 AHB-Lite Protocol Specification, ver. 1.0, June 06, 2006. [Online] www.eecs.umich.edu/~prabal/teaching/eecs373/f10/readings/ARM_IHI0033A_AMBA_AHBLite_SPEC.pdf
- [21] ARM, "AMBA AXI Protocol Specifications," ver.1.0, June 16, 2003. [Online] www.home.mit.bme.hu/~feher/MSC_RA/ARM/AMBAaxi%5B1%5D.pdf
- [22] Altera Avalon, Avalon bus specification: Reference manual. Altera Corporation, July, 2003. Available online at <http://www.altera.com>
- [23] Altera, Avalon interface specification Altera Corporation, April, 2005. [Online] <http://www.altera.com>
- [24] Altera, "Simultaneous Multi-Mastering with the Avalon Bus," Application Note 184, Version 1.1, p.2, April 2002.
- [25] Rudolf Usselmann, "OpenCores SoC Bus Review," Rev. 1.0, pp.1-12, January 9, 2001. www.opencores.org
- [26] Patrick Pelgrims, Tom Tierens and Dries Driessens, "OVERVIEW -- AMBA, AVALON, CORECONNECT, WISHBONE," Version 1.1, DE NAYER Institute, pp. 1-6, 2003. Available online at <http://www.opencontent.org/openpub/>
- [27] M. Mitic et al. "An overview of on chip buses", FACTA Universitatis Series: Electronics and Energetics, 19(3), pp. 405-428, December 2006.
- [28] ALTERA Corporation "Quartus II Software Licensing Questions and Answers," Available online at www.altera.com/download/licensing/q-and-a/lic-qii_q_and_a.html
- [29] P. J. Aldworth, "System-on-a-Chip Bus Architecture for Embedded Applications," (ICCD'99) International Conference on Computer Design, pp. 297 -298, 1999.

[30] Richard Herveille, "WISHBONE System-on-Chip (SoC) Interconnection Architecture for Portable IP Cores," Specification Rev. B3, September 7, 2002.

[31] Medardoni Simone, "Driving the Network-on-Chip Revolution to Remove the Interconnect Bottleneck in Nanoscale Multi-Processor Systems-on-Chip," Research Thesis: Università degli Studi di Ferrara, p. 17, 2008.

[32] Wishfaq.htm Silicore Corporation p.4, page updated: March 18, 2002.

[33] Rudolf Usselmann, "OpenCores SoC Bus Review," Rev. 1.0, p. 12, January 9, 2001.

A New Approach to Design Low Power CMOS Flash A/D Converter

Sudakar S. Chauhan¹, S. Manabala², S.C. Bose³ and R. Chandel⁴

¹Department of Electronics & Communication Engineering, Graphic Era University, Dehradun, India

^{2,3}Central Electronics Engineering Research Institute (CEERI), Pilani, India

⁴Department of Electronics & Communication Engineering, National Institute of Technology, Hamirpur, India

ABSTRACT

In the present paper, a 4-bit flash analog to digital converter for low power SoC application is presented. CMOS inverter has been used as a comparator and by adjusting the ratio of channel width and length, the switching threshold of the CMOS inverter is varied to detect the input analog signal. The simulation results show that this proposed 4-bit flash ADC consumes about 12.4 mW at 200M sample/s with 3.3V supply voltage in TSMC 0.35 μm process. Compared with the traditional flash ADC, this proposed method can reduce about 78% in power consumption.

KEYWORDS

CMOS Inverter, XOR gate based encoder, Flash ADC.

For More Details: <https://airconline.com/vlsics/V2N2/2211vlsics08.pdf>

Volume Link: <https://airccse.org/journal/vlsi/vol2.html>

REFERENCES

- [1] C. Chun Tsai, Kai-Wei Hong, Yuh-Shyan Hwang, Wen-Ta Lee and Trong-Yen Lee, "New Power saving design method for CMOS flash ADC," The 2004 47th Midwest Symposium on Circuits and Systems, vol. 3. pp. 371-374, July 2004.
- [2] W. Ta Lee, P. Hsiang Huang, Y. Zhen Liao, and Y. Shyan Hwang, "A New Low-Power Flash ADC Using Multiple Section Method," IEEE Conference on Electron Devices and Solid-State Circuits, EDSSC 2007, pp. 341-344, 20-22 Dec. 2007.
- [3] M. Wang and C. H. Chen, "Design Synthesis and Performance Measurement of Pipelined Flash ADC for SoC Application", Proceeding of the 2005 IEEE Instrumentation and Measurement Technology Conference, pp.19-24, Ottawa, Ontario, Canada, USA, May 17-19, 2005.
- [4] M. Wang and C. H. Chen, "Architecture and Design Synthesis of 2.5 GS/s 4-bit Pipelined Flash ADC for SoC Application", Proc. Of the 31st Annual Conference of the

IEEE Industrial Electronic Society, pp. 2224-2230, Raleigh, North Carolina, USA, Nov. 6-10, 2005.

[5] A. Stojcevski, H. P. Le, J. Singh and A. Zayegh, "Flash ADC architecture", IEE Electronics Letters, vol.39, no.6, pp. 501-502, March 2003.

[6] S. Banik, D. Gangopadhyay and T. K. Bhattacharyya, "A Low Power 1.8V 4-bit 400Mhz Flash ADC in 0.18 μm CMOS", Proc. Of the 19th International Conference On VLSI Design (VLSID'06).

[7] C. W. Hsu and T. H. Kuo, "6-bit 500 Mhz Flash ADC with new design Techniques", IEE Proc. Circuits Devices Syst., vol.150, no.5, pp. 460-464, Oct. 2003.

[8] W. Song, H. Choi, S. Kwak and B. Song, "A 10-bit 20MS/s Low Power CMOS ADC", IEEE J.Solid-State Circuits, vol. 30, pp. 514-520 May 1995.

[9] G. M. Yin, F. Eynde and W. Sansen, "A High Speed CMOS Comparator with 8-bit Resolution", IEEE J. Solid-State Circuits, vol. 27, pp. 208-211, Feb. 1992.

[10] V. Ferrazina, N. Ghittori and F. Maloberti, "Low Power 6-bit Flash ADC for High Speed Data Converters Architectures", IEEE Symposium on Circuits and Systems, pp. 3930-3933, 2006.

[11] M. Choi and A. A. Abidi, "A 6-bit 1.3GS/s A/D converter in 0.35 μm CMOS," IEEE Journal of Solid-State Circuits, vol.36, Dec.2001, pp. 1847-1858.

[12] K. Uyttenhove and M. S. J. Steyaert, "A 1.8-V 6-bit 1.3 GHz flash ADC in 0.25 μm CMOS" IEEE Journal of Solid-State Circuits, vol.38, July 2003, pp. 1115-1122.

[13] P. C. S. Scholtens and M. Vertregt, "A 6-bit 1.6 GS/s Flash ADC in 0.18 μm CMOS using Averaging Termination", IEEE Journal of Solid-State Circuits, pp. 1599-1609, 2002.

[14] S. Chang Hsia, Wen- Ching Lee, "A Very Low Power Flash A/D Converter Based on CMOS Inverter Circuit," IDEAS'05, pp. 107-110, July 2005.

[15] A. Tangel and K. Choi, "CMOS Inverter as a comparator in ADC design," in Proc. ICEEE, 2001, pp. 1-5.

[16] S. M. Kang and Y. Leblebici, CMOS Digital Integrated Circuits Analysis and Design, Tata McGraw-Hill Edition 2003.

[17] S. Akiyama and Takao Waho, "A 6-bit Low-Power Compact Flash ADC Using Current-Mode Threshold Logic Gates." IEEE Symposium on Circuits and Systems, pp.3938-3941, 2006.

- [18] S. Sheikhaei, S. Mirabbasi and A. Ivanov, "A 4 bit 5 GS/s Flash ADC in 0.18 μm CMOS", IEEE Symposium on Circuits and Systems (ISCAS), pp. 6138-6141, May 2005.
- [19] C. Sander, M. Clara, A. Santner, T. Hartig and F. Kuttner, "A 6-bit 1.2 GS/s Low Power Flash ADC in 0.13 μm CMOS", IEEE Journal of Solid-State Circuits, vol. 40, no. 7, pp. 1499-1505, July 2005.
- [20] D. A. Johns and K. martin, Analog Integrated Circuit Design, John Wiley & Sons 2002.